

200 Series

Width 8.74" (222mm), length 19.70" (500mm)
Load class E 600 kN

Ductile iron slotted grating



Product Features:

- Certified to EN 1433 Load Class E 600 kN - 134,800 lbs.
- Uses fiX self-locking system.
- Suitable to use with NW200 channels.
- Manufactured from ductile iron.

Installation:

- The trench drain system and grates shall be installed in accordance with the manufacturer's installation instructions and recommendations.

Gratings 200 series (8.74") with fix self locking system.

	Item no.	Gratings	Material	Dimention	Load class as per EN- standard	Slot-/Mesh width	Weight		Inlet cross- section sq.inches	Inlet cross- section cm2/m
							Lbs	Kg		
○	17020105	Ductile iron slotted grating	ductile iron	19.70"/8.74"/0.78" 500/222/20	E 600 kN	0.55" wide x 7.87" slots (SW 14x200 mm)	18.96	8.6	110.58	965

Specification: 200, extra heavy duty, (Load Class E 600 kN), ductile iron, reinforced grate is 8.74" (222mm) wide, 19.70" (500mm) long, 0.78" (20mm) high, weighing 18.96 lbs (8.6 kg). The grate has 0.55" (14mm) wide, 7.87" (200mm) long slot and is Class E load rated - for commercial solid tire traffic patters, and impacts from steel struts or metal wheels (forklifts). The grate is secured to the body with four point fiX self-locking (snap-on) system. Galvanized steel manufactured and tested according to EN1433 - CE certified.

Rating: Load Class E, Forklift Rated, Airport Rated, Heavy Duty Drainage System.
EN1433 - CE certified

E600kN SW14/200: GJS 17020105

